

<b>Plum Creek AC Sanded Plywood</b>	
<b>SPECS</b>	<ul style="list-style-type: none"> <li>• Slow growth inland Douglas Fir and Larch yield fine-grained, smooth faces</li> <li>• All Group 1, Struc 1 Species</li> </ul>
<b>FACES</b>	<ul style="list-style-type: none"> <li>• "A" grade veneer</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• 15 plug average assures the highest face quality</li> <li>• Fully sanded face</li> </ul>
<b>BACKS, CENTERS &amp; CORES</b>	<ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade or better center and back</li> </ul>
<b>CONSTRUCTION &amp; THICKNESS</b>	<p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4' x 8'</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed panels to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> <li>• Underlayment stamp available</li> </ul>