

<b>Plum Creek Douglas Fir Siding</b>	
<b>SPECS</b>	<ul style="list-style-type: none"> <li>• Inland western Douglas Fir known for its slow growth, fine texture and tight grain</li> <li>• All Group 1, Struc 1 Species</li> <li>• Finishing characteristics well-suited for paint, heavy body or semi-transparent stain</li> <li>• High ply count construction ensures superior strength and stability</li> </ul>
<b>FACES</b>	<ul style="list-style-type: none"> <li>• APA "A" grade face</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Average 14 plugs per panel</li> </ul>
<b>BACKS, CENTERS &amp; CORES</b>	<ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade center and back</li> </ul>
<b>CONSTRUCTION &amp; THICKNESS</b>	<p><b>Thickness Ply count</b></p> <p>3/8"      4 Ply No Groove</p> <p>1/2"      5 Ply No Groove, 4" OC, 8" OC</p> <p>5/8"      5 Ply No Groove, 4" OC, 8" OC</p> <ul style="list-style-type: none"> <li>• Scarfed 9' and 10' available</li> <li>• Rough texture or scratch sand</li> <li>• Ship lap or square edge</li> </ul>