

<b>Plum Creek MDO Sign Grade</b>	
<b>SPECS</b>	<ul style="list-style-type: none"> <li>• A quality Medium Density Overlay plywood product</li> <li>• All Group 1, Struc 1 Species</li> <li>• One or two-step process</li> </ul>
<b>FACES</b>	<ul style="list-style-type: none"> <li>• "B" grade veneer under paper</li> <li>• Wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Pre-primed paper available</li> <li>• One or two side panel available in one or two step process</li> <li>• Fully sanded face with two step process</li> </ul>
<b>BACKS, CENTERS &amp; CORES</b>	<ul style="list-style-type: none"> <li>• Plum Creek's High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece "C" grade or better center and back</li> <li>• Primed one side panels produced with a backer sheet</li> </ul>
<b>CONSTRUCTION &amp; THICKNESS</b>	<p><b>Thickness Ply count</b></p> <p>3/8"      4 Ply</p> <p>1/2"      5 Ply</p> <p>5/8"      5 or 7 Ply</p> <p>3/4"      7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4' x 8'</li> <li>• Scarfed panels to 10'</li> </ul>