

<b>Plum Creek MarineDeck™</b>	
<b>SPECS</b>	<ul style="list-style-type: none"> <li>• Designed for rigorous marine use with superior “CP” grade face</li> <li>• All Group 1, Struc 1 Species</li> <li>• Available with solid core under the face</li> <li>• 2 side panels available</li> </ul>
<b>FACES</b>	<ul style="list-style-type: none"> <li>• “C” plugged grade veneer</li> <li>• Quality wood plugs or putty repairs, minimal use of polyurethane patch</li> <li>• Splits over 1/16” are filled. Sound, tight knots up to 1 1/2"</li> <li>• Face is touch sanded with 60 grit paper</li> </ul>
<b>BACKS, CENTERS &amp; CORES</b>	<ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade or better center and back</li> </ul>
<b>CONSTRUCTION &amp; THICKNESS</b>	<p><b>Thickness Ply count</b></p> <p>1/4"     3 Ply</p> <p>3/8"     4 Ply</p> <p>1/2"     5 Ply</p> <p>5/8"     5 or 7 Ply</p> <p>3/4"     7 Ply</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• Panel thickness to 1 1/2"</li> <li>• Solid long length to 102"</li> <li>• Scarfed length to 16'</li> <li>• Tongue and groove available on 5/8" - 1 1/8"</li> <li>• Underlayment stamp available</li> </ul>