

<b>Plum Creek Ultra-Pour™ HDO Concrete Form</b>	
<b>SPECS</b>	<ul style="list-style-type: none"> <li>• Two-Step process</li> <li>• All Group 1, Struc 1 Species</li> <li>• Highest quality edge seal</li> </ul>
<b>FACES</b>	<ul style="list-style-type: none"> <li>• APA “B” grade face</li> <li>• Smooth uniform finish enhances durability of product</li> <li>• Increased pours</li> <li>• Minimum grain transfer</li> </ul>
<b>BACKS, CENTERS &amp; CORES</b>	<ul style="list-style-type: none"> <li>• Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs</li> <li>• One piece “C” grade center and back</li> </ul>
<b>CONSTRUCTION &amp; THICKNESS</b>	<p><b>Thickness Ply count</b></p> <p>1/2"      5 Ply 100/30 100/100 120/30 120/120</p> <p>5/8"      7 Ply 100/30 100/100 120/30 120/120</p> <p>3/4"      7 Ply 100/30 100/100 120/30 120/120</p> <ul style="list-style-type: none"> <li>• Standard size 4’ x 8’</li> <li>• 2’ x 8’ size available</li> <li>• Full thick</li> </ul>